

NAME

IPC::Semaphore - SysV Semaphore IPC object class

SYNOPSIS

```
use IPC::SysV qw(IPC_PRIVATE S_IRUSR S_IWUSR IPC_CREAT);
use IPC::Semaphore;

$sem = IPC::Semaphore->new(IPC_PRIVATE, 10, S_IRUSR | S_IWUSR |
IPC_CREAT);

$sem->setall( (0) x 10);

@sem = $sem->getall;

$ncnt = $sem->getncnt;

$zcnt = $sem->getzcnt;

$ds = $sem->stat;

$sem->remove;
```

DESCRIPTION

A class providing an object based interface to SysV IPC semaphores.

METHODS

`new (KEY , NSEMS , FLAGS)`

Create a new semaphore set associated with `KEY`. `NSEMS` is the number of semaphores in the set. A new set is created if

- `KEY` is equal to `IPC_PRIVATE`
- `KEY` does not already have a semaphore identifier associated with it, and `FLAGS` & `IPC_CREAT` is true.

On creation of a new semaphore set `FLAGS` is used to set the permissions. Be careful not to set any flags that the Sys V IPC implementation does not allow: in some systems setting execute bits makes the operations fail.

`getall`

Returns the values of the semaphore set as an array.

`getncnt (SEM)`

Returns the number of processes waiting for the semaphore `SEM` to become greater than its current value

`getpid (SEM)`

Returns the process id of the last process that performed an operation on the semaphore `SEM`.

`getval (SEM)`

Returns the current value of the semaphore `SEM`.

`getzcnt (SEM)`

Returns the number of processes waiting for the semaphore `SEM` to become zero.

`id`

Returns the system identifier for the semaphore set.

`op (OPLIST)`

`OPLIST` is a list of operations to pass to `semop`. `OPLIST` is a concatenation of smaller lists, each which has three values. The first is the semaphore number, the second is the operation and the last is a flags value. See *semop* for more details. For example

```
$sem->op(  
  0, -1, IPC_NOWAIT,  
  1,  1, IPC_NOWAIT  
);
```

`remove`

Remove and destroy the semaphore set from the system.

`set (STAT)`

`set (NAME => VALUE [, NAME => VALUE ...])`

`set` will set the following values of the `stat` structure associated with the semaphore set.

```
uid  
gid  
mode (only the permission bits)
```

`set` accepts either a `stat` object, as returned by the `stat` method, or a list of *name-value* pairs.

`setall (VALUES)`

Sets all values in the semaphore set to those given on the `VALUES` list. `VALUES` must contain the correct number of values.

`setval (N , VALUE)`

Set the `N`th value in the semaphore set to `VALUE`

`stat`

Returns an object of type `IPC::Semaphore::stat` which is a sub-class of `Class::Struct`. It provides the following fields. For a description of these fields see your system documentation.

```
uid  
gid  
cuid  
cgid  
mode  
ctime  
otime  
nsems
```

SEE ALSO

IPC::SysV, *Class::Struct*, *semget*, *semctl*, *semop*

AUTHORS

Graham Barr <gbarr@pobox.com>, Marcus Holland-Moritz <mhx@cpan.org>

COPYRIGHT

Version 2.x, Copyright (C) 2007, Marcus Holland-Moritz.

Version 1.x, Copyright (c) 1997, Graham Barr.

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.