

NAME

Module::CoreList - what modules shipped with versions of perl

SYNOPSIS

```
use Module::CoreList;

print $Module::CoreList::version{5.00503}{CPAN}; # prints 1.48

print Module::CoreList->first_release('File::Spec');      # prints
5.00405
print Module::CoreList->first_release_by_date('File::Spec'); # prints
5.005
print Module::CoreList->first_release('File::Spec', 0.82);  # prints
5.006001

print join ' ', ' ', Module::CoreList->find_modules(qr/Data/);
# prints 'Data::Dumper'
print join ' ', ' ', Module::CoreList->find_modules(qr/test::h.*::.*s/i,
5.008008);
# prints 'Test::Harness::Assert, Test::Harness::Straps'

print join ", ", "@{ $Module::CoreList::families{5.005} }";
# prints "5.005, 5.00503, 5.00504"
```

DESCRIPTION

Module::CoreList provides information on which core and dual-life modules shipped with each version of *perl*.

It provides a number of mechanisms for querying this information.

There is a utility called *corelist* provided with this module which is a convenient way of querying from the command-line.

There is a functional programming API available for programmers to query information.

Programmers may also query the contained hash structures to find relevant information.

FUNCTIONS API

These are the functions that are available, they may either be called as functions or class methods:

```
Module::CoreList::first_release('File::Spec'); # as a function
```

```
Module::CoreList->first_release('File::Spec'); # class method
```

```
first_release( MODULE )
```

Behaviour since version 2.11

Requires a MODULE name as an argument, returns the perl version when that module first appeared in core as ordered by perl version number or undef (in scalar context) or an empty list (in list context) if that module is not in core.

```
first_release_by_date( MODULE )
```

Requires a MODULE name as an argument, returns the perl version when that module first appeared in core as ordered by release date or undef (in scalar context) or an empty list (in list context) if that module is not in core.

`find_modules(REGEX, [LIST OF PERLS])`

Takes a regex as an argument, returns a list of modules that match the regex given. If only a regex is provided applies to all modules in all perl versions. Optionally you may provide a list of perl versions to limit the regex search.

`find_version(PERL_VERSION)`

Takes a perl version as an argument. Returns that perl version if it exists or `undef` otherwise.

`is_deprecated(MODULE, PERL_VERSION)`

Available in version 2.22 and above.

Returns true if `MODULE` is marked as deprecated in `PERL_VERSION`. If `PERL_VERSION` is omitted, it defaults to the current version of Perl.

`removed_from(MODULE)`

Available in version 2.32 and above

Takes a module name as an argument, returns the first perl version where that module was removed from core. Returns `undef` if the given module was never in core or remains in core.

`removed_from_by_date(MODULE)`

Available in version 2.32 and above

Takes a module name as an argument, returns the first perl version by release date where that module was removed from core. Returns `undef` if the given module was never in core or remains in core.

DATA STRUCTURES

These are the hash data structures that are available:

`%Module::CoreList::version`

A hash of hashes that is keyed on perl version as indicated in `$]`. The second level hash is `module => version` pairs.

Note, it is possible for the version of a module to be unspecified, whereby the value is `undef`, so use `exists $version{$foo}{$bar}` if that's what you're testing for.

Starting with 2.10, the special module name `Unicode` refers to the version of the Unicode Character Database bundled with Perl.

`%Module::CoreList::released`

Keyed on perl version this contains ISO formatted versions of the release dates, as gleaned from *perlhst*.

`%Module::CoreList::families`

New, in 1.96, a hash that clusters known perl releases by their major versions.

`%Module::CoreList::deprecated`

A hash of hashes keyed on perl version and on module name. If a module is defined it indicates that that module is deprecated in that perl version and is scheduled for removal from core at some future point.

`%Module::CoreList::upstream`

A hash that contains information on where patches should be directed for each core module.

UPSTREAM indicates where patches should go. `undef` implies that this hasn't been discussed for the module at hand. `blead` indicates that the copy of the module in the blead sources is to be considered canonical, `cpan` means that the module on CPAN is to be patched first. `first-come` means that blead can be patched freely if it is in sync with the latest release on CPAN.

`%Module::CoreList::bug_tracker`

A hash that contains information on the appropriate bug tracker for each core module.

BUGS is an email or url to post bug reports. For modules with UPSTREAM => 'blead', use `perl5-porters@perl.org`. `rt.cpan.org` appears to automatically provide a URL for CPAN modules; any value given here overrides the default:

`http://rt.cpan.org/Public/Dist/Display.html?Name=$ModuleName`

CAVEATS

Module::CoreList currently covers the 5.000, 5.001, 5.002, 5.003_07, 5.004, 5.004_05, 5.005, 5.005_03, 5.005_04, 5.6.0, 5.6.1, 5.6.2, 5.7.3, 5.8.0, 5.8.1, 5.8.2, 5.8.3, 5.8.4, 5.8.5, 5.8.6, 5.8.7, 5.8.8, 5.8.9, 5.9.0, 5.9.1, 5.9.2, 5.9.3, 5.9.4, 5.9.5, 5.10.0, 5.10.1, 5.11.0, 5.11.1, 5.11.2, 5.11.3, 5.11.4, 5.11.5, 5.12.0, 5.12.1, 5.12.2, 5.12.3, 5.12.4, 5.12.5, 5.13.0, 5.13.1, 5.13.2, 5.13.3, 5.13.4, 5.13.5, 5.13.6, 5.13.7, 5.13.8, 5.13.9, 5.13.10, 5.13.11, 5.14.0 and 5.14.1 releases of perl.

HISTORY

Moved to Changes file.

AUTHOR

Richard Clamp <richardc@unixbeard.net>

Currently maintained by the perl 5 porters <perl5-porters@perl.org>.

LICENSE

Copyright (C) 2002-2009 Richard Clamp. All Rights Reserved.

This module is free software; you can redistribute it and/or modify it under the same terms as Perl itself.

SEE ALSO

corelist, *Module::Info*, *perl*