

## NAME

CPANPLUS::Internals::Utils - convenience functions for CPANPLUS

## SYNOPSIS

```
my $bool = $cb->_mkdir( dir => 'blah' );
my $bool = $cb->_chdir( dir => 'blah' );
my $bool = $cb->_rmdir( dir => 'blah' );

my $bool = $cb->_move( from => '/some/file', to => '/other/file' );
my $bool = $cb->_move( from => '/some/dir', to => '/other/dir' );

my $cont = $cb->_get_file_contents( file => '/path/to/file' );

my $version = $cb->_perl_version( perl => $^X );
```

## DESCRIPTION

CPANPLUS::Internals::Utils holds a few convenience functions for CPANPLUS libraries.

## METHODS

### **\$cb->\_mkdir( dir => '/some/dir' )**

`_mkdir` creates a full path to a directory.

Returns true on success, false on failure.

### **\$cb->\_chdir( dir => '/some/dir' )**

`_chdir` changes directory to a dir.

Returns true on success, false on failure.

### **\$cb->\_rmdir( dir => '/some/dir' );**

Removes a directory completely, even if it is non-empty.

Returns true on success, false on failure.

### **\$cb->\_perl\_version ( perl => 'some/perl/binary' );**

`_perl_version` returns the version of a certain perl binary. It does this by actually running a command.

Returns the perl version on success and false on failure.

### **\$cb->\_version\_to\_number( version => \$version );**

Returns a proper module version, or '0.0' if none was available.

### **\$cb->\_whoami**

Returns the name of the subroutine you're currently in.

### **\_get\_file\_contents( file => \$file );**

Returns the contents of a file

### **\$cb->\_move( from => \$file\$dir, to => \$target );**

Moves a file or directory to the target.

Returns true on success, false on failure.

**\$cb->\_copy( from => \$file,\$dir, to => \$target );**

Moves a file or directory to the target.

Returns true on success, false on failure.

**\$cb->\_mode\_plus\_w( file => '/path/to/file' );**

Sets the +w bit for the file.

Returns true on success, false on failure.

**\$uri = \$cb->\_host\_to\_uri( scheme => SCHEME, host => HOST, path => PATH );**

Turns a CPANPLUS::Config style `host` entry into an URI string.

Returns the uri on success, and false on failure

**\$cb->\_vcmp( VERSION, VERSION );**

Normalizes the versions passed and does a '<=>' on them, returning the result.

**\$cb->\_home\_dir**

Returns the user's homedir, or `cwd` if it could not be found

**\$path = \$cb->\_safe\_path( path => \$path );**

Returns a path that's safe to us on Win32 and VMS.

Only cleans up the path on Win32 if the path exists.

On VMS, it encodes dots to `_` using `VMS::Filespec::vmsify`

**(\$pkg, \$version, \$ext) = \$cb->\_split\_package\_string( package => PACKAGE\_STRING );**

Splits the name of a CPAN package string up into its package, version and extension parts.

For example, `Foo-Bar-1.2.tar.gz` would return the following parts:

```
Package:    Foo-Bar
Version:    1.2
Extension:  tar.gz
```