

## NAME

CPAN::Distroprefs -- read and match distroprefs

## SYNOPSIS

```
use CPAN::Distroprefs;

my %info = (... distribution/environment info ...);

my $finder = CPAN::Distroprefs->find($prefs_dir, \%ext_map);

while (my $result = $finder->next) {

    die $result->as_string if $result->is_fatal;

    warn($result->as_string), next if $result->is_warning;

    for my $pref (@{ $result->prefs }) {
        if ($pref->matches(\%info)) {
            return $pref;
        }
    }
}
```

## DESCRIPTION

This module encapsulates reading *Distroprefs* and matching them against CPAN distributions.

## INTERFACE

```
my $finder = CPAN::Distroprefs->find($dir, \%ext_map);

while (my $result = $finder->next) { ... }
```

Build an iterator which finds distroprefs files in the given directory.

`%ext_map` is a hashref whose keys are file extensions and whose values are modules used to load matching files:

```
{
    'yaml' => 'YAML::Syck',
    'dd'   => 'Data::Dumper',
    ...
}
```

Each time `$finder->next` is called, the iterator returns one of two possible values:

- \* a `CPAN::Distroprefs::Result` object
- \* `undef`, indicating that no prefs files remain to be found

## RESULTS

`find()` returns `CPAN::Distroprefs::Result` objects to indicate success or failure when reading a prefs file.

## Common

All results share some common attributes:

### type

success, warning, or fatal

### file

the file from which these prefs were read, or to which this error refers (relative filename)

### ext

the file's extension, which determines how to load it

### dir

the directory the file was read from

### abs

the absolute path to the file

## Errors

Error results (warning and fatal) contain:

### msg

the error message (usually either \$! or a YAML error)

## Successes

Success results contain:

### prefs

an arrayref of CPAN::Distroprefs::Pref objects

## PREFS

CPAN::Distroprefs::Pref objects represent individual distroprefs documents. They are constructed automatically as part of `success` results from `find()`.

### data

the pref information as a hashref, suitable for e.g. passing to Kwalify

### match\_attributes

returns a list of the valid match attributes (see the Distroprefs section in *CPAN*)

currently: `env perl perlconfig distribution module`

### has\_any\_match

true if this pref has a 'match' attribute at all

### has\_valid\_subkeys

true if this pref has a 'match' attribute and at least one valid match attribute

### matches

```
if ($pref->matches(\%arg)) { ... }
```

true if this pref matches the passed-in hashref, which must have a value for each of the `match_attributes` (above)

**LICENSE**

This program is free software; you can redistribute it and/or modify it under the same terms as Perl itself.