

NAME

pod2usage - print usage messages from embedded pod docs in files

SYNOPSIS

pod2usage

[-help] [-man] [-exit *exitval*] [-output *outfile*] [-verbose *level*] [-pathlist *dirlist*] [-formatter *module*] *file*

OPTIONS AND ARGUMENTS

-help

Print a brief help message and exit.

-man

Print this command's manual page and exit.

-exit *exitval*

The exit status value to return.

-output *outfile*

The output file to print to. If the special names "-" or ">&1" or ">&STDOUT" are used then standard output is used. If ">&2" or ">&STDERR" is used then standard error is used.

-verbose *level*

The desired level of verbosity to use:

1 : print SYNOPSIS only
2 : print SYNOPSIS sections and any OPTIONS/ARGUMENTS sections
3 : print the entire manpage (similar to running pod2text)

-pathlist *dirlist*

Specifies one or more directories to search for the input file if it was not supplied with an absolute path. Each directory path in the given list should be separated by a ':' on Unix ';' on MSWin32 and DOS).

-formatter *module*

Which text formatter to use. Default is *Pod::Text*, or for very old Perl versions *Pod::PlainText*. An alternative would be e.g. *Pod::Text::Termcap*.

file

The pathname of a file containing pod documentation to be output in usage message format (defaults to standard input).

DESCRIPTION

pod2usage will read the given input file looking for pod documentation and will print the corresponding usage message. If no input file is specified then standard input is read.

pod2usage invokes the **pod2usage()** function in the **Pod::Usage** module. Please see "*pod2usage()*" in *Pod::Usage*.

SEE ALSO

Pod::Usage, *pod2text(1)*

AUTHOR

Please report bugs using <http://rt.cpan.org>.

Brad Appleton <bradapp@enteract.com>

Based on code for **pod2text(1)** written by Tom Christiansen <tchrist@mox.perl.com>