

NAME

CPANPLUS::Shell::Default

SYNOPSIS

```
### loading the shell:
$ cpanp                # run 'cpanp' from the command line
$ perl -MCPANPLUS -eshell  # load the shell from the command line

use CPANPLUS::Shell qw[Default];      # load this shell via the API
                                       # always done via

CPANPLUS::Shell

my $ui = CPANPLUS::Shell->new;
$ui->shell;                            # run the shell
$ui->dispatch_on_input( input => 'x');  # update the source using the
                                       # dispatch method

### when in the shell:
### Note that all commands can also take options.
### Look at their underlying CPANPLUS::Backend methods to see
### what options those are.
cpanp> h                # show help messages
cpanp> ?                # show help messages

cpanp> m Acme           # find acme modules, allows regexes
cpanp> a KANE           # find modules by kane, allows regexes
cpanp> f Acme::Foo      # get a list of all releases of Acme::Foo

cpanp> i Acme::Foo      # install Acme::Foo
cpanp> i Acme-Foo-1.3   # install version 1.3 of Acme::Foo
cpanp> i <URI>          # install from URI, like ftp://foo.com/X.tgz
cpanp> i <DIR>          # install from an absolute or relative
directory
cpanp> i 1 3..5         # install search results 1, 3, 4 and 5
cpanp> i *              # install all search results
cpanp> a KANE; i *;     # find modules by kane, install all results
cpanp> t Acme::Foo     # test Acme::Foo, without installing it
cpanp> u Acme::Foo     # uninstall Acme::Foo
cpanp> d Acme::Foo     # download Acme::Foo
cpanp> z Acme::Foo     # download & extract Acme::Foo, then open a
                        # shell in the extraction directory

cpanp> c Acme::Foo     # get a list of test results for Acme::Foo
cpanp> l Acme::Foo     # view details about the Acme::Foo package
cpanp> r Acme::Foo     # view Acme::Foo's README file
cpanp> o               # get a list of all installed modules that
                        # are out of date
cpanp> o 1..3         # list uptodateness from a previous search

cpanp> s conf          # show config settings
cpanp> s conf md5 1    # enable md5 checks
cpanp> s program       # show program settings
cpanp> s edit          # edit config file
```

```
cpanp> s reconfigure      # go through initial configuration again
cpanp> s selfupdate       # update your CPANPLUS install
cpanp> s save             # save config to disk
cpanp> s mirrors          # show currently selected mirrors

cpanp> ! [PERL CODE]     # execute the following perl code

cpanp> b                  # create an autobundle for this computers
                        # perl installation
cpanp> x                  # reload index files (purges cache)
cpanp> x --update_source  # reload index files, get fresh source files
cpanp> p [FILE]           # print error stack (to a file)
cpanp> v                  # show the banner
cpanp> w                  # show last search results again

cpanp> q                  # quit the shell

cpanp> /plugins           # list avialable plugins
cpanp> /? PLUGIN          # list help test of <PLUGIN>

### common options:
cpanp> i ... --skiptest   # skip tests
cpanp> i ... --force     # force all operations
cpanp> i ... --verbose   # run in verbose mode
```

DESCRIPTION

This module provides the default user interface to CPANPLUS. You can start it via the `cpanp` binary, or as detailed in the *SYNOPSIS*.

BUG REPORTS

Please report bugs or other issues to <bug-cpanplus@rt.cpan.org>.

AUTHOR

This module by Jos Boumans <kane@cpan.org>.

COPYRIGHT

The CPAN++ interface (of which this module is a part of) is copyright (c) 2001 - 2007, Jos Boumans <kane@cpan.org>. All rights reserved.

This library is free software; you may redistribute and/or modify it under the same terms as Perl itself.

SEE ALSO

CPANPLUS::Shell::Classic, *CPANPLUS::Shell*, *cpanp*