

NAME

ExtUtils::MM_Any - Platform-agnostic MM methods

SYNOPSIS

FOR INTERNAL USE ONLY!

```
package ExtUtils::MM_SomeOS;

# Temporarily, you have to subclass both. Put MM_Any first.
require ExtUtils::MM_Any;
require ExtUtils::MM_Unix;
@ISA = qw(ExtUtils::MM_Any ExtUtils::Unix);
```

DESCRIPTION

FOR INTERNAL USE ONLY!

ExtUtils::MM_Any is a superclass for the ExtUtils::MM_* set of modules. It contains methods which are either inherently cross-platform or are written in a cross-platform manner.

Subclass off of ExtUtils::MM_Any *and* ExtUtils::MM_Unix. This is a temporary solution.

THIS MAY BE TEMPORARY!

METHODS

Any methods marked *Abstract* must be implemented by subclasses.

Cross-platform helper methods

These are methods which help writing cross-platform code.

os_flavor Abstract

```
my @os_flavor = $mm->os_flavor;
```

@os_flavor is the style of operating system this is, usually corresponding to the MM_*.pm file we're using.

The first element of @os_flavor is the major family (ie. Unix, Windows, VMS, OS/2, etc...) and the rest are sub families.

Some examples:

| | |
|----------|--|
| Cygwin98 | ('Unix', 'Cygwin', 'Cygwin9x') |
| Windows | ('Win32') |
| Win98 | ('Win32', 'Win9x') |
| Linux | ('Unix', 'Linux') |
| MacOS X | ('Unix', 'Darwin', 'MacOS', 'MacOS X') |
| OS/2 | ('OS/2') |

This is used to write code for styles of operating system. See os_flavor_is() for use.

os_flavor_is

```
my $is_this_flavor = $mm->os_flavor_is($this_flavor);
my $is_this_flavor = $mm->os_flavor_is(@one_of_these_flavors);
```

Checks to see if the current operating system is one of the given flavors.

This is useful for code like:

```
if( $mm->os_flavor_is('Unix') ) {  
    $out = `foo 2>&l`;  
}  
else {  
    $out = `foo`;  
}
```

can_load_xs

```
my $can_load_xs = $self->can_load_xs;
```

Returns true if we have the ability to load XS.

This is important because miniperl, used to build XS modules in the core, can not load XS.

can_run

```
use ExtUtils::MM;  
my $runnable = MM->can_run($Config{make});
```

If called in a scalar context it will return the full path to the binary you asked for if it was found, or undef if it was not.

If called in a list context, it will return a list of the full paths to instances of the binary where found in PATH, or an empty list if it was not found.

Copied from *IPC::Cmd*, but modified into a method (and removed \$INSTANCES capability).

can_redirect_error

```
$userredirect = MM->can_redirect_error;
```

True if on an OS where qx operator (or backticks) can redirect STDERR onto STDOUT.

is_make_type

```
my $is_dmake = $self->is_make_type('dmake');
```

Returns true if <\$self-make> is the given type; possibilities are:

```
gmake      GNU make  
dmake  
nmake  
bsdmake    BSD pmake-derived
```

can_dep_space

```
my $can_dep_space = $self->can_dep_space;
```

Returns true if make can handle (probably by quoting) dependencies that contain a space. Currently known true for GNU make, false for BSD pmake derivative.

quote_dep

```
$text = $mm->quote_dep($text);
```

Method that protects Makefile single-value constants (mainly filenames), so that make will still treat them as single values even if they inconveniently have spaces in. If the make program being used cannot achieve such protection and the given text would need it, throws an exception.

split_command

```
my @cmds = $MM->split_command($cmd, @args);
```

Most OS have a maximum command length they can execute at once. Large modules can easily generate commands well past that limit. Its necessary to split long commands up into a series of shorter commands.

`split_command` will return a series of `@cmds` each processing part of the args. Collectively they will process all the arguments. Each individual line in `@cmds` will not be longer than the `$self->max_exec_len` being careful to take into account macro expansion.

`$cmd` should include any switches and repeated initial arguments.

If no `@args` are given, no `@cmds` will be returned.

Pairs of arguments will always be preserved in a single command, this is a heuristic for things like `pm_to_blib` and `pod2man` which work on pairs of arguments. This makes things like this safe:

```
$self->split_command($cmd, %pod2man);
```

echo

```
my @commands = $MM->echo($text);  
my @commands = $MM->echo($text, $file);  
my @commands = $MM->echo($text, $file, \%opts);
```

Generates a set of `@commands` which print the `$text` to a `$file`.

If `$file` is not given, output goes to STDOUT.

If `$opts{append}` is true the `$file` will be appended to rather than overwritten. Default is to overwrite.

If `$opts{allow_variables}` is true, make variables of the form `$(...)` will not be escaped. Other `$` will. Default is to escape all `$`.

Example of use:

```
my $make = map "\t$_\n", $MM->echo($text, $file);
```

wraplist

```
my $args = $mm->wraplist(@list);
```

Takes an array of items and turns them into a well-formatted list of arguments. In most cases this is simply something like:

```
FOO \  
BAR \  
BAZ
```

maketext_filter

```
my $filter_make_text = $mm->maketext_filter($make_text);
```

The text of the Makefile is run through this method before writing to disk. It allows systems a chance to make portability fixes to the Makefile.

By default it does nothing.

This method is protected and not intended to be called outside of `MakeMaker`.

cd Abstract

```
my $subdir_cmd = $MM->cd($subdir, @cmds);
```

This will generate a make fragment which runs the @cmds in the given \$dir. The rough equivalent to this, except cross platform.

```
cd $subdir && $cmd
```

Currently \$dir can only go down one level. "foo" is fine. "foo/bar" is not. "../foo" is right out.

The resulting \$subdir_cmd has no leading tab nor trailing newline. This makes it easier to embed in a make string. For example.

```
my $make = sprintf <<'CODE', $subdir_cmd;
foo :
    $(ECHO) what
    %s
    $(ECHO) mouche
CODE
```

oneliner Abstract

```
my $oneliner = $MM->oneliner($perl_code);
my $oneliner = $MM->oneliner($perl_code, \@switches);
```

This will generate a perl one-liner safe for the particular platform you're on based on the given \$perl_code and @switches (a -e is assumed) suitable for using in a make target. It will use the proper shell quoting and escapes.

\$(PERLRUN) will be used as perl.

Any newlines in \$perl_code will be escaped. Leading and trailing newlines will be stripped. Makes this idiom much easier:

```
my $code = $MM->oneliner(<<'CODE', [...switches...]);
some code here
another line here
CODE
```

Usage might be something like:

```
# an echo emulation
$oneliner = $MM->oneliner('print "Foo\n"');
$make = '$oneliner > somefile';
```

All dollar signs must be doubled in the \$perl_code if you expect them to be interpreted normally, otherwise it will be considered a make macro. Also remember to quote make macros else it might be used as a bareword. For example:

```
# Assign the value of the $(VERSION_FROM) make macro to $vf.
$oneliner = $MM->oneliner('$${vf} = "$(VERSION_FROM)";
```

Its currently very simple and may be expanded sometime in the future to include more flexible code and switches.

quote_literal Abstract

```
my $safe_text = $MM->quote_literal($text);  
my $safe_text = $MM->quote_literal($text, \%options);
```

This will quote \$text so it is interpreted literally in the shell.

For example, on Unix this would escape any single-quotes in \$text and put single-quotes around the whole thing.

If \$options{allow_variables} is true it will leave '\$(FOO)' make variables untouched. If false they will be escaped like any other \$. Defaults to true.

escape_dollarsigns

```
my $escaped_text = $MM->escape_dollarsigns($text);
```

Escapes stray \$ so they are not interpreted as make variables.

It lets by \$(...).

escape_all_dollarsigns

```
my $escaped_text = $MM->escape_all_dollarsigns($text);
```

Escapes all \$ so they are not interpreted as make variables.

escape_newlines Abstract

```
my $escaped_text = $MM->escape_newlines($text);
```

Shell escapes newlines in \$text.

max_exec_len Abstract

```
my $max_exec_len = $MM->max_exec_len;
```

Calculates the maximum command size the OS can exec. Effectively, this is the max size of a shell command line.

make

```
my $make = $MM->make;
```

Returns the make variant we're generating the Makefile for. This attempts to do some normalization on the information from %Config or the user.

Targets

These are methods which produce make targets.

all_target

Generate the default target 'all'.

blibdirs_target

```
my $make_frag = $mm->blibdirs_target;
```

Creates the blibdirs target which creates all the directories we use in blib/.

The blibdirs.ts target is deprecated. Depend on blibdirs instead.

clean (o)

Defines the clean target.

clean_subdirs_target

```
my $make_frag = $MM->clean_subdirs_target;
```

Returns the clean_subdirs target. This is used by the clean target to call clean on any subdirectories which contain Makefiles.

dir_target

```
my $make_frag = $mm->dir_target(@directories);
```

Generates targets to create the specified directories and set its permission to PERM_DIR.

Because depending on a directory to just ensure it exists doesn't work too well (the modified time changes too often) dir_target() creates a .exists file in the created directory. It is this you should depend on. For portability purposes you should use the \$(DIRFILESEP) macro rather than a '/' to separate the directory from the file.

```
yourdirectory$(DIRFILESEP).exists
```

distdir

Defines the scratch directory target that will hold the distribution before tar-ing (or shar-ing).

dist_test

Defines a target that produces the distribution in the scratch directory, and runs 'perl Makefile.PL; make ;make test' in that subdirectory.

dynamic (o)

Defines the dynamic target.

makemakerdflt_target

```
my $make_frag = $mm->makemakerdflt_target
```

Returns a make fragment with the makemakerdflt_target specified. This target is the first target in the Makefile, is the default target and simply points off to 'all' just in case any make variant gets confused or something gets snuck in before the real 'all' target.

manifypods_target

```
my $manifypods_target = $self->manifypods_target;
```

Generates the manifypods target. This target generates man pages from all POD files in MAN1PODS and MAN3PODS.

metafile_target

```
my $target = $mm->metafile_target;
```

Generate the metafile target.

Writes the file META.yml (YAML encoded meta-data) and META.json (JSON encoded meta-data) about the module in the distdir. The format follows Module::Build's as closely as possible.

`_fix_metadata_before_conversion`

```
_fix_metadata_before_conversion( \%metadata );
```

Fixes errors in the metadata before it's handed off to CPAN::Meta for conversion. This hopefully results in something that can be used further on, no guarantee is made though.

`_sort_pairs`

```
my @pairs = _sort_pairs($sort_sub, \%hash);
```

Sorts the pairs of a hash based on keys ordered according to \$sort_sub.

`metafile_data`

```
my @metadata_pairs = $mm->metafile_data(\%meta_add, \%meta_merge);
```

Returns the data which MakeMaker turns into the META.yml file and the META.json file.

Values of %meta_add will overwrite any existing metadata in those keys. %meta_merge will be merged with them.

`_dump_hash`

```
$yaml = _dump_hash(\%options, %hash);
```

Implements a fake YAML dumper for a hash given as a list of pairs. No quoting/escaping is done. Keys are supposed to be strings. Values are undef, strings, hash refs or array refs of strings.

Supported options are:

```
delta => STR - indentation delta
use_header => BOOL - whether to include a YAML header
indent => STR - a string of spaces
               default: ''

max_key_length => INT - maximum key length used to align
                    keys and values of the same hash
               default: 20
key_sort => CODE - a sort sub
               It may be undef, which means no sorting by keys
               default: sub { lc $a cmp lc $b }

customs => HASH - special options for certain keys
               (whose values are hashes themselves)
               may contain: max_key_length, key_sort, customs
```

`metafile_file`

```
my $meta_yaml = $mm->metafile_file(@metadata_pairs);
```

Turns the @metadata_pairs into YAML.

This method does not implement a complete YAML dumper, being limited to dump a hash with values which are strings, undef's or nested hashes and arrays of strings. No quoting/escaping is done.

`distmeta_target`

```
my $make_frag = $mm->distmeta_target;
```

Generates the distmeta target to add META.yml and META.json to the MANIFEST in the distdir.

mymeta

```
my $mymeta = $mm->mymeta;
```

Generate MYMETA information as a hash either from an existing CPAN Meta file (META.json or META.yml) or from internal data.

write_mymeta

```
$self->write_mymeta( $mymeta );
```

Write MYMETA information to MYMETA.json and MYMETA.yml.

realclean (o)

Defines the realclean target.

realclean_subdirs_target

```
my $make_frag = $MM->realclean_subdirs_target;
```

Returns the realclean_subdirs target. This is used by the realclean target to call realclean on any subdirectories which contain Makefiles.

signature_target

```
my $target = $mm->signature_target;
```

Generate the signature target.

Writes the file SIGNATURE with "cpansign -s".

distsignature_target

```
my $make_frag = $mm->distsignature_target;
```

Generates the distsignature target to add SIGNATURE to the MANIFEST in the distdir.

special_targets

```
my $make_frag = $mm->special_targets
```

Returns a make fragment containing any targets which have special meaning to make. For example, .SUFFIXES and .PHONY.

Init methods

Methods which help initialize the MakeMaker object and macros.

init_ABSTRACT

```
$mm->init_ABSTRACT
```

init_INST

```
$mm->init_INST;
```

Called by init_main. Sets up all INST_* variables except those related to XS code. Those are handled in init_xs.

init_INSTALL

```
$mm->init_INSTALL;
```

Called by `init_main`. Sets up all `INSTALL_*` variables (except `INSTALLDIRS`) and `*PREFIX`.

init_INSTALL_from_PREFIX

```
$mm->init_INSTALL_from_PREFIX;
```

init_from_INSTALL_BASE

```
$mm->init_from_INSTALL_BASE
```

init_VERSION Abstract

```
$mm->init_VERSION
```

Initialize macros representing versions of MakeMaker and other tools

MAKEMAKER: path to the MakeMaker module.

MM_VERSION: ExtUtils::MakeMaker Version

MM_REVISION: ExtUtils::MakeMaker version control revision (for backwards compat)

VERSION: version of your module

VERSION_MACRO: which macro represents the version (usually 'VERSION')

VERSION_SYM: like version but safe for use as an RCS revision number

DEFINE_VERSION: -D line to set the module version when compiling

XS_VERSION: version in your .xs file. Defaults to \$(VERSION)

XS_VERSION_MACRO: which macro represents the XS version.

XS_DEFINE_VERSION: -D line to set the xs version when compiling.

Called by `init_main`.

init_tools

```
$MM->init_tools();
```

Initializes the simple macro definitions used by `tools_other()` and places them in the `$MM` object. These use conservative cross platform versions and should be overridden with platform specific versions for performance.

Defines at least these macros.

| Macro | Description |
|--------|---|
| NOOP | Do nothing |
| NOECHO | Tell make not to display the command itself |
| SHELL | Program used to run shell commands |
| ECHO | Print text adding a newline on the end |
| RM_F | Remove a file |
| RM_RF | Remove a directory |

| | |
|-------------|--------------------------------|
| TOUCH | Update a file's timestamp |
| TEST_F | Test for a file's existence |
| TEST_S | Test the size of a file |
| CP | Copy a file |
| CP_NONEMPTY | Copy a file if it is not empty |
| MV | Move a file |
| CHMOD | Change permissions on a file |
| FALSE | Exit with non-zero |
| TRUE | Exit with zero |
| | |
| UMASK_NULL | Nullify umask |
| DEV_NULL | Suppress all command output |

init_others

```
$MM->init_others();
```

Initializes the macro definitions having to do with compiling and linking used by tools_other() and places them in the \$MM object.

If there is no description, its the same as the parameter to WriteMakefile() documented in ExtUtils::MakeMaker.

tools_other

```
my $make_frag = $MM->tools_other;
```

Returns a make fragment containing definitions for the macros init_others() initializes.

init_DIRFILESEP Abstract

```
$MM->init_DIRFILESEP;  
my $dirfilesep = $MM->{DIRFILESEP};
```

Initializes the DIRFILESEP macro which is the separator between the directory and filename in a filepath. ie. / on Unix, \ on Win32 and nothing on VMS.

For example:

```
# instead of $(INST_ARCHAUTODIR)/extralibs.ld  
$(INST_ARCHAUTODIR)$ (DIRFILESEP)extralibs.ld
```

Something of a hack but it prevents a lot of code duplication between MM_* variants.

Do not use this as a separator between directories. Some operating systems use different separators between subdirectories as between directories and filenames (for example: VOLUME:[dir1.dir2]file on VMS).

init_linker Abstract

```
$mm->init_linker;
```

Initialize macros which have to do with linking.

PERL_ARCHIVE: path to libperl.a equivalent to be linked to dynamic extensions.

PERL_ARCHIVE_AFTER: path to a library which should be put on the linker command line *after* the external libraries to be linked to dynamic extensions. This may be needed if the linker is one-pass, and Perl includes some overrides for C RTL functions, such as malloc().

EXPORT_LIST: name of a file that is passed to linker to define symbols to be exported.

Some OSes do not need these in which case leave it blank.

init_platform

```
$mm->init_platform
```

Initialize any macros which are for platform specific use only.

A typical one is the version number of your OS specific module. (ie. MM_Unix_VERSION or MM_VMS_VERSION).

init_MAKE

```
$mm->init_MAKE
```

Initialize MAKE from either a MAKE environment variable or \$Config{make}.

Tools

A grab bag of methods to generate specific macros and commands.

manifypods

Defines targets and routines to translate the pods into manpages and put them into the INST_* directories.

POD2MAN_macro

```
my $pod2man_macro = $self->POD2MAN_macro
```

Returns a definition for the POD2MAN macro. This is a program which emulates the pod2man utility. You can add more switches to the command by simply appending them on the macro.

Typical usage:

```
$(POD2MAN) --section=3 --perm_rw=$(PERM_RW) podfile1 man_page1 ...
```

test_via_harness

```
my $command = $mm->test_via_harness($perl, $tests);
```

Returns a \$command line which runs the given set of \$tests with Test::Harness and the given \$perl.

Used on the t/*.t files.

test_via_script

```
my $command = $mm->test_via_script($perl, $script);
```

Returns a \$command line which just runs a single test without Test::Harness. No checks are done on the results, they're just printed.

Used for test.pl, since they don't always follow Test::Harness formatting.

tool_autosplit

Defines a simple perl call that runs autosplit. May be deprecated by pm_to_blib soon.

arch_check

```
my $arch_ok = $mm->arch_check(  
    $INC{"Config.pm"},  
    File::Spec->catfile($Config{archlibexp}, "Config.pm")
```

```
);
```

A sanity check that what Perl thinks the architecture is and what Config thinks the architecture is are the same. If they're not it will return false and show a diagnostic message.

When building Perl it will always return true, as nothing is installed yet.

The interface is a bit odd because this is the result of a quick refactoring. Don't rely on it.

File::Spec wrappers

ExtUtils::MM_Any is a subclass of File::Spec. The methods noted here override File::Spec.

catfile

File::Spec <= 0.83 has a bug where the file part of catfile is not canonicalized. This override fixes that bug.

Misc

Methods I can't really figure out where they should go yet.

find_tests

```
my $test = $mm->find_tests;
```

Returns a string suitable for feeding to the shell to return all tests in t/*.t.

find_tests_recursive

```
my $tests = $mm->find_tests_recursive;
```

Returns a string suitable for feeding to the shell to return all tests in t/ but recursively.

extra_clean_files

```
my @files_to_clean = $MM->extra_clean_files;
```

Returns a list of OS specific files to be removed in the clean target in addition to the usual set.

installvars

```
my @installvars = $mm->installvars;
```

A list of all the INSTALL* variables without the INSTALL prefix. Useful for iteration or building related variable sets.

libscan

```
my $wanted = $self->libscan($path);
```

Takes a path to a file or dir and returns an empty string if we don't want to include this file in the library. Otherwise it returns the the \$path unchanged.

Mainly used to exclude version control administrative directories from installation.

platform_constants

```
my $make_frag = $mm->platform_constants
```

Returns a make fragment defining all the macros initialized in init_platform() rather than put them in constants().

_PREREQ_PRINT

```
$self->_PREREQ_PRINT;
```

Implements PREREQ_PRINT.

Refactored out of MakeMaker->new().

_PRINT_PREREQ

```
$mm->_PRINT_PREREQ;
```

Implements PRINT_PREREQ, a slightly different version of PREREQ_PRINT added by Redhat to, I think, support generating RPMs from Perl modules.

Should not include BUILD_REQUIRES as RPMs do not include them.

Refactored out of MakeMaker->new().

_all_prereqs

```
my $prereqs = $self->_all_prereqs;
```

Returns a hash ref of both PREREQ_PM and BUILD_REQUIRES.

_perl_header_files

```
my $perl_header_files= $self->_perl_header_files;
```

returns a sorted list of header files as found in PERL_SRC or \$archlibexp/CORE.

Used by perldepend() in MM_Unix and MM_VMS via _perl_header_files_fragment()

_perl_header_files_fragment (\$o, \$separator)

```
my $perl_header_files_fragment= $self->_perl_header_files_fragment("/");
```

return a Makefile fragment which holds the list of perl header files which XS code depends on \$(PERL_INC), and sets up the dependency for the \$(OBJECT) file.

The \$separator argument defaults to "". MM_VMS will set it to "" and MM_UNIX to "/" in perldepend(). This reason child subclasses need to control this is that in VMS the \$(PERL_INC) directory will already have delimiters in it, but in UNIX \$(PERL_INC) will need a slash between it and the filename. Hypothetically win32 could use "\\" (but it doesn't need to).

AUTHOR

Michael G Schwern <schwern@pobox.com> and the denizens of makemaker@perl.org with code from ExtUtils::MM_Unix and ExtUtils::MM_Win32.